USB KVM SPLITTER

Allows two users to control one USB computer and connect three USB devices



VOPEX-USBV-2 (Front & Back)

Features & Applications

The VOPEX[®] USB KVM Splitter with built-in USB hub allows two users (two USB keyboards, USB mice and VGA monitors) to access one USB-enabled computer and up to three USB devices (printers, scanners, security cameras, etc.).

- Compatible with USB PC, SUN and MAC computers.
- Built-in hub for multiple USB devices.
- Access one computer from multiple locations.
- Multiple users can enter data into the same program.
- Both low speed and full speed USB devices are supported.
- USB 1.1 compliant.
- Supports Plug-n-Play specifications.
- Supports international keyboard layouts in auto-detection mode.

Specifications

Devices

Hosts

- Male 15-pin HD connector.
- Female USB Type B connector.
- Supports SUN BladeTM 100, SUN Blade 1000, SUN RayTM, SUN FireTM 240, and SUN Fire V20z.
- Supports PCs with USB-enabled OS (Win 98/2000/XP) and USB ports.
- Supports PCs with USB-enabled BIOS (legacy USB support) and USB ports.
- Supports MAC G4, G5 and Xserve.

Monitor

- Female 15-pin HD connectors.
- Crisp and clear 1900x1200 resolution.
- Bandwidth is 150 MHz.

Power

■ 110 or 220 VAC at 50 or 60 Hz via AC adapter.

Control Modes

- Press Mode button to cycle through all four modes. LEDs indicate which mode is selected.
- User 1 Mode–only User 1 can type or move mouse.
- User 2 Mode–only User 2 can type or move mouse.
- Inst Mode-keyboard or mouse activates immediately
- Delay Mode-locked out user must wait five seconds after last keystroke or mouse movement occurs on active user.

Cables

• Three-foot female 15HD, male USB Type B to male 15HD, male USB Type A cable included.

- Female USB Type A connectors for connection of keyboard and mouse.
 - Compatible with most USB keyboards and mice, including Microsoft USB Intellimouse®, Logitech Cordless Elite Duo keyboard and mouse, Gyration keyboard/mouse and Crystal Vision keyboard with touchpad.
 - Keyboard and mouse are hot-pluggable.
- Three female USB Type A connectors for connection of USB peripheral devices (printers, scanners, security cameras, etc.)
- Compliant with USB 1.1 specifications.

Dimensions

WxDxH (in): 8.5x6.0x2.6


Regulatory Approvals

• CE, UL, cUL, FCC, RoHS

Warranty

Two years

Configuration and Cable Illustration





1.800.RGB.TECH (800.742.8324) 330.56 Toll Free: US & Canada Internation ©2006-2007, NTI. All rights reserved.

330.562.7070 330. International calls Worl

330.562.1999 Worldwide fax sales@ntigo.com www.networktechinc.co

VOPEX®